

**Model SHAFTLESS SCREW CONVEYOR – Quote Information Sheet**  
**Fax: (519) 881-3573**

Project: \_\_\_\_\_ Email: \_\_\_\_\_

Contact: \_\_\_\_\_ Phone: \_\_\_\_\_

Company Address: \_\_\_\_\_ Fax: \_\_\_\_\_

Status: \_\_\_\_\_ initial design / \_\_\_\_\_ final design / \_\_\_\_\_ quotation

Conveyed Medium (screenings, sludge, etc): \_\_\_\_\_

Medium Apparent Density (lb/cu.ft OR kg/cu.m): \_\_\_\_\_

Design Loading Rate (cu.ft/h OR cu.m/h): \_\_\_\_\_

Conveyor Inclination (degree): \_\_\_\_\_ Trough Length (ft OR m), \_\_\_\_\_

Materials of Construction (check one):

Trough & Hoppers; Carbon steel \_\_\_ / 304 SS \_\_\_ / 316 SS \_\_\_

Supports; Carbon steel \_\_\_ / 304 SS \_\_\_ / 316 SS \_\_\_

Shaftless Screw; Carbon steel \_\_\_\_\_ / stainless steel \_\_\_\_\_

Installation; indoor \_\_\_\_\_ outdoor \_\_\_\_\_

Area Classification (check one):

Explosion Proof (NEMA / EEMAC 7) \_\_\_\_\_

Weather Proof & Corrosion Proof (NEMA / EEMAC 4X) \_\_\_\_\_

Other \_\_\_\_\_

Power Supply Available: VAC \_\_\_\_\_ / phase \_\_\_\_\_ / Hz \_\_\_\_\_

Electrical Controls: by others \_\_\_\_\_ / included (describe) \_\_\_\_\_

Safety Features to be included (Y/N)

Rope shut-off switch at inlets (optional) \_\_\_\_\_

Auto shut-off if cover opened (optional) \_\_\_\_\_

Loss of motion detector (optional) \_\_\_\_\_

Further Details / Special Conditions / Dimensional Restrictions:

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_